

Example of 'HPMV flexibility' permit application

c12. Total Mass Applied For (tonnes) * 50	c13. Load (circle) * <u>Divisible</u> / Indivisible
c14. Axle weight flexibility (AWF) Required (circle) * <u>Yes</u> No	c15. AWF limits (circle): Class <u>1/HPMV</u> /User defined

c16. Axle Number	1	2	3	4	5	6	7	8	9	10
c17. Axle Type ^(†)	S	S	T	T	T	T	T	T		
c18. Tyre Size ^(†)	ST	ST	ST	ST	ST	ST	ST	ST		
c19. Suspension Type ^(††)	L	L	AD	AD	L	L	L	L		
c20. Track Outer (m) ^(††)	2.2	2.2	2.0	2.0	2.0	2.0	2.0	2.0		
c21. Mass (tonnes) ^(††)	5	5	7.0	7.0	6.5	6.5	6.5	6.5		
c22. Max Mass (user defined)**										
c23. Spacing from prev (m) ^(††)	1.9	3.57	1.32	4.9	1.25	4.10	1.25			
c24. Axle group ^(††)	TS	TS	T	T	T	T	T	T		
c25. Steering axle ^(††)	<u>Y</u> /N	<u>Y</u> /N	Y/ <u>N</u>	Y/ <u>N</u>	Y/ <u>N</u>	Y/ <u>N</u>	Y/ <u>N</u>	Y/ <u>N</u>	Y/N	Y/N

- c21 must be filled in with the expected typical operational axle masses, that add to the total mass applied for (c12).
- By requesting 'HPMV' AWF (c15), axles, axle sets and pairs of axle sets may vary up to the HPMV limits in Tables 1 to 6 of Schedule 2 Part B (Mass Limits for HPMV) of the VDM Rule 2002. See [Factsheet 13g High-Productivity Motor Vehicles](#) for more information.
- c22 should be left blank, as User-defined AWF has not been requested.